

Product Overview

LV8075LP: Motor Driver, Forward / Reverse, 1-Channel, Constant Voltage Control

For complete documentation, see the data sheet

Product Description

The LV8075LP is a low voltage, bidirectional DC motor driver with a typical input voltage of 2.5 to 5.5 V and output currents up to 500 mA. The unique output full-bridge incorporates source-side linear operation to allow a constant voltage across the motor coil. Internal protection circuitry includes thermal shutdown and under voltage lockout.

Features

- Low voltage control from 2.5 V
- Output ON Resistance : 1.75ohm(Upper and Lower Total)
- Low Voltage Operation 2.5Vmin
- VCT Package

Benefits

- Battery drive suitable
- High Efficiency
- Low Input Voltage Device Available
- Small Design Footprint

Applications

Portable & Wireless

- End Products
 - Digital Still Camera
 - Portable Device, Camera, Game, Small Printer

Part Electrical Specifications

Product	Compliance	Status	Туре	V _M Min (V)	V _M Max (V)	V _{CC} Min (V)	V _{CC} Max (V)	l _o Max (A)	l _o Peak Max (A)	Contr ol Type	Feed back Meth od	Curre nt Sens e	Regu lator Outp ut	Fault Dete ction	Flyba ck Prote ction	Pack age Type
LV8075LP-E	Pb-free	Active	Brus h DC	2.5	6	2.5	6	0.5		Paral lel	None	None	No	The rma I UV LO	Integ rated Activ e	VCT- 16
LV8075LP-TE-L-E	Pb-free	Active	Brus h DC	2.5	6	2.5	6	0.5	-	Paral lel	None	None	No	The rma I UV LO	Integ rated Activ e	VCT- 16

For more information please contact your local sales support at www.onsemi.com

Created on: 10/11/2013